

Features

- ◆ USB 1.1/2.0 compliant bus
- ◆ Support for the following audio formats: Stereo, Mono, Dual Language (Mono), Tri Language (Trivox)
- ◆ Three I²C master ports (two ports are provided for a two-tuner design to isolate I²C transactions to reduce noise)
- ◆ Macrovision 1.0 Detection Compliant
- ◆ Support for the following video formats: Composite, S-Video, 480i YPrPb, RGB Packed, YCrCb Packed, 10-bit Packed, and YCrCb/YUY2 Format
- ◆ Advanced consumer IR functionality enables systems to receive, learn, and blast IR signals
- ◆ High-quality multi-tap horizontal and vertical image scaler for decoded video or 4:2:2 sources
- ◆ I²S out
- ◆ Auxiliary Phase Locked Loop (PLL) clock for general use
- ◆ Flexible video input MUX supporting composite, S-Video, and component inputs with integrated anti-alias filtering
- ◆ Integrated sigma-delta stereo audio ADCs with 4:2 MUX
- ◆ Audio sample rate converters on all inputs and outputs
- ◆ Two MPEG transport stream ports: Parallel and Serial
- ◆ Two program stream inputs accommodating serial or parallel interfaces
- ◆ ITU-R BT.656 output port

The CX23103 brings Conexant's long heritage of audio and video capture solutions to systems that enable universal serial bus architectures. The CX23103 integrates all the functions required to perform external A/V capture on personal computers or consumer electronic devices.

The CX23103 integrates anti-aliasing, noise rejection filters and automatic gain control (AGC). Quality video is accomplished by using 10-bit video ADCs, a full 10-bit video data path, and a horizontal and 5-tap vertical scaling, hue, brightness, saturation, and contrast controls.

For high-quality audio, the CX23103 has analog to digital converters for stereo audio capture and a minimum of 16-bit audio resolution through the entire audio data path which ensures high fidelity audio. The audio path includes an automatic volume control function and two assignable stereo processing units for control of volume, three-band equalization, and balance. The level of audio and video integration provided by the CX23103 removes the need for additional audio ADCs and processing chips or USB bridge chip. It also reduces the overall bill of materials (BOM) for the system developer, without compromising audio and video performance.



Description USB Audio/Video Decoder

